

# **Nexion interprets Stone**

#### LITHIC COLLECTION

Lithic revisits the innate beauty of the natural stone according to Nexion designer style which opens the boundaries to new technical features with the revolutionary **Absolute Matte** finishing.

Four new aesthetics emulate the vivid and realistic shades of natural stone and harmonize the graphics of nature by representing it in sintered stone.

#### **Brightness, texture and Absolute Matte:**

world's finest materials are re-design and enhanced by an incomparable research and design process to give the material the right texture, touch and look; Nexion present a new revolution in matt surfaces: Absolute Matte, an unparallel soft touch surface without compromising on anti slippery and anti-reflective technical performance of sintered stone.

Lithic offers impeccable aesthetic solutions together with the highest technical qualities of Nexion sintered stone.

The collection comes in four colors: **Roccia Portoghese**, inspired by the beige limestone, Vicenza Beige, the classic pale sedimentary stone, Basalto Grigio, the dark volcanic rock and Gabbro Sfumato, gray with muted tones.

#### **Nexion about**

Nexion is a brand of Nexion Surfaces, a multinational ceramic company that is the result of a partnership between two large family groups that have always been leaders in their reference markets: Ceramiche Speranza, the best in its class Italian firm founded in 1961, that has setup the state of the art manufacturing facilities in India together with the Aghara family, one of the leading players in ceramics and sanitary ware in India since 1977.

With mastery of technology and design, we turn the best of the Italian tradition and lifestyle into contemporary ceramic surfaces that can be source of inspiration for architects and designers around the world.

Open-minded and keen to learn from customers and partners, we are committed to deliver the best quality and service and we believe that our work ends when our clients fulfill their desires and achieve their goals.

Design, Marketing & Global Sales Via 2 Giugno, 13 41042 Fiorano Modenese Modena(Italy) globalcs@nexiontiles.com www.nexiontiles.com


Headquarters & Indian Sales **Nexion Surfaces Private Limited** 1104-1105, Shapath V, S. G. Highway, Ahmedabad - 380 015, Gujarat (India) indiancs@nexiontiles.com www.nexiontiles.com

Full body-colored porcelain stoneware (International standard) | Vitrified stoneware (Indian standard) Rectified | 9 mm thickness









Roccia Portoghese 120x240 cm F14LTCB1SR0 Absolute Matte



Roccia Portoghese 80x160 cm F86LTCB1SRO Absolute Matte



Roccia Portoghese 120x120 cm F12LTCB1SR0 Absolute Matte



Roccia Portoghese 60x120 cm F62LTCB1SRO Absolute Matte



Roccia Portoghese 60x60 cm F60LTCB1SR0 Absolute Matte



Roccia Portoghese 30x60 cm

F63LTCB1SRO Absolute Matte



Vicenza Beige 120x240 cm F14LTCBOSRO Absolute Matte



Basalto Grigio 120x240 cm F14LTCG0SR0 Absolute Matte




Gabbro Sfumato 120x240 cm F14LTCKOSRO Absolute Matte



F86LTCBOSRO Absolute Matte



F86LTCGOSRO Absolute Matte



Gabbro Sfumato 80x160 cm F86LTCKOSRO Absolute Matte



Vicenza Beige 120x120 cm F12LTCBOSRO Absolute Matte



Basalto Grigio 120x120 cm F12LTCGOSRO Absolute Matte



Gabbro Sfumato 120x120 cm F12LTCKOSRO Absolute Matte



Vicenza Beige 60x60 cm

Vicenza Beige 30x60 cm

F63LTCB0SR0 Absolute Matte

F60LTCB0SR0 Absolute Matte

Vicenza Beige 60x120 cm







Basalto Grigio 60x120 cm F62LTCGOSRO Absolute Matte



Basalto Grigio 60x60 cm

Basalto Grigio 30x60 cm

F63LTCGOSRO Absolute Matte

F60LTCG0SR0 Absolute Matte

Gabbro Sfumato 60x120 cm F62LTCKOSRO Absolute Matte





Gabbro Sfumato 60x60 cm F60LTCKOSRO Absolute Matte





Gabbro Sfumato 30x60 cm F63LTCKOSRO Absolute Matte

### Nexion installation suggestions

Nexion recommends 2 mm joint for optimal aesthetics taking advantage of the tiles caliber in multi-sized applications. Both cement and epoxy grout can be used; grout-design color matching advisable for optimal aesthetics. It is not recommended to use grouting with colored pigments in contrast with the color of the tiles. For detailed installation guidelines log on www.nexiontiles.com

### **Nexion quality standards**

ALL TESTS ARE CARRIED OUT BY ITALIAN LABORATORIES ACCREDITED ACCORDING TO ISO/IEC 17025:2017 Standards according to ISO 13006: Annex G - EN 14411: Annex G. Dry - Pressed Ceramic Tiles.

QUALITY ITEMS	TECHNICAL FEATURE	STANDARD METHOD ISO	UNIT	REOUIREMENTS	NEXION Values			
				REQUIREMENTS ISO 13006:2018(E) E <sub>V</sub> ≤0,5% GROUP Bla	SIZE < 1200 mm		SIZE ≥ 1200 mm (SLABS)	
					%	mm	%	mm
DIMENSIONS AND SURFACE QUALITY	Width	ISO 10545 - 2	mm	± 0,3%	± 0,1%	± 0,8 mm	± 0,1%	± 1,0 mm
	Length	ISO 10545 - 2	mm	± 0,3%	± 0,1%	± 0,8 mm	± 0,1%	± 1,2 mm
	Thickness	ISO 10545 - 2	mm	± 5,0%	± 4,0%	± 0,5 mm	± 4,0%	± 0,5 mm
	Straightness of Side	ISO 10545 - 2	mm	± 0,3%	± 0,1%	± 0,8 mm	± 0,1%	± 1,0 mm
	Rectangularity	ISO 10545 - 2	mm	± 0,3%	± 0,1%	± 1,3 mm	± 0,1%	± 1,5 mm
	Surface Flatness	ISO 10545 - 2	mm	± 0,4%	± 0,1%	± 1,8 mm	± 0,2%	± 3,0 mm
	Surface Quality	ISO 10545 - 2	-	A minimum of 95% of the tiles are to be free from visible defects which can impair the appearance of a major area of tiles	95%			
	Water Absorption	ISO 10545 - 3	%	≤ 0,5%, Individual 0,6%	Avg. ≤ 0,08%, Individual 0,2%			
	Modulus of Rupture	ISO 10545 - 4	N/mm <sup>2</sup>	Min. 35, Individual Min. 32	Min. 42			
	Breaking Strength	ISO 10545 - 4	N	Not less than 1300	Min. 1800			
	Moisture Expansion	ISO 10545 - 10	mm/m	-	0,02			
	Surface Abrasion		Class	Minimum Class II	Class IV (> 2100 Cycles)			
	Resistance to surface abrasion of glazed tiles intended for use on floors	ISO 10545 - 7		Report abrasion class and cycles passed				
	Mohs Hardness of surface	NA	-	-	7			
PHYSICAL PROPERTIES	Coefficient of linear thermal expansion from ambient temperature to 100 °C	ISO 10545 - 8	K-1	As declared by the Manufacturer	6x10 <sup>-6</sup> K <sup>-1</sup> max			
	Thermal Shock Resistance	ISO 10545 - 9	-	As declared by the Manufacturer	No damage			
	Crazing Resistance: glazed tiles	ISO 10545 - 11	-	Required	No damage for Min. 10 Cycles			
	Bulk Density	ISO 10545 - 3	g/cc	2,2	2,2			
	Impact Resistance	ISO 10545 - 5	-	As declared by the Manufacturer	0,55			
	Frost Resistance	ISO 10545 - 12	-	As declared by the Manufacturer	No change			
	Slip Resistance	ANSI A137,1	-	As declared by the Manufacturer	DCOF > 0,51			
		DIN 51130	-	As decialed by the Mandiacturer	R-10			
	Small color differences	ISO 10545 - 16	-	Plain colored tiles only where required GL: ΔE < 0,75 UGL: ΔE < 1,0	No change			
	Resistance to staining	ISO 10545 - 14	Class	Minimum Class 3	Class 4			
CHEMICAL PROPERTIES	Resistance to household chemicals and swimming pool salts	ISO 10545 - 13	Class	Minimum B	Minimum A			
	Resistance to acids & alkalis	ISO 10545 - 13	Class	As declared by the Manufacturer	Minimum B			

## Packaging info

Shipments	to domestic ma	rkets (India)		
Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)
120x240	9	1	2,87	61,00
80x160	9	2	2,55	54,00
120x120	9	2	2,87	60,00
60x120	9	2	1,43	30,00
60x60	9	4	1,43	31,00
30x60	9	6	1,07	23,00

Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. mt x pallet	Pallet weight (Kg)
120x240	9	1	2,87	61,00	37	106,30	2347,00
80x160	9	2	2,55	54,00	28	71,40	1582,00
120x120	9	2	2,87	60,00	24	68,88	1510,00
60x120	9	2	1,43	30,00	32	45,82	1003,00
60x60	9	4	1,43	31,00	34	48,69	1077,00
30x60	9	6	1,07	23,00	40	42,72	943,00

Minimum B				
Size				
Nominal Size cm	Actual Size cm			
120x240	119,8x239,8			
80x160	79,8x159,8			
120x120	119,8x119,8			
60x120	59,8x119,8			
60x60	59,8x59,8			
30x60	29,8x59,8			



